



ANICLEAN PASTA

Anilox cylinder paste cleaning agent

Developed for the preventive and deep cleaning of the anilox cylinder, without the need to disassemble it off-press. Excellent for water based inks and varnishes, due to its high cleaning power. ANICLEAN PASTA has a very stable formulation, carefully developed for the highly demanding print shops where production downtime needs to be optimized.

Properties

- High cleaning capacity paste cleaner.
- It prevents premature cells plugging appearance.
- For deep cleaning it can be used out of press, but for preventive cleaning, apply directly on the anilox assembled on press.
- Non aggressive formulation. It does not attack ceramic or steel anilox. Not for use with aluminum anilox.
- Low foam formation.
- Adequate for use with hard waters.

User's instructions

Maintenance cleaning: It is conducted with the anilox assembled on the press. When it is done on a weekly basis, the anilox cells premature obstruction can be avoided. **Warning:** Photopolymers can not be exposed to this cleaning product.

Apply generously **Aniclean Paste** all along the anilox cylinder and extend it uniformly while turning the anilox, than leave it to act from 10 minutes up to 2 hours according to the cleaning needs. After, rinse it off with plenty water via the press ink circulation system.

Deep cleaning for anilox already plugged: The anilox cylinder needs to be taken-out from the press and once it is off, the cleaning can be done.

Apply the **Aniclean Paste** thoroughly over the whole anilox surface and leave it to act from 1 to 6 hours, than rinse it off with plenty water. Finally apply cold water at high pressure.

In case the anilox is not satisfactorily cleaned, repeat the cleaning process.